



<p>[1-1] PCB 1.6mm thick DUMMY-CHIP 25.0mm SQ 3.5mm thick HEATSINK LPD50-25B 42.0g CLIP CQZL40-55 ANCHOR CNCR-12 TIM YG6260 TOTAL FORCE 2.4 kgf (23.7N) 5.5PSI</p>	<p>[2] PCB 1.6mm thick DUMMY-CHIP 25.0mm SQ 5.0mm thick HEATSINK LPD60-25B 65.0g CLIP CQZL40-65 ANCHOR CNCR-12 TIM YG6260 TOTAL FORCE 2.7 kgf (26.3N) 6.1PSI</p>	<p>[3] PCB 5.0mm thick DUMMY-CHIP 25.0mm SQ 5.0mm thick HEATSINK LPD60-9.6B 45.0g CLIP CQZL40-55 ANCHOR CNCR-16 TIM YG6260 TOTAL FORCE 2.7 kgf (26.3N) 6.1PSI</p>
<p>[1-2] PCB 1.6mm thick DUMMY-CHIP 25mm SQ 2.0mm thick HEATSINK LPD40-7B 15.0g CLIP CQZL40-45 ANCHOR CNCR-8 TIM YG6260 TOTAL FORCE 3.1 kgf (30.6N) 7.1PSI</p>		
<p>[4] PCB 1.6mm thick DUMMY-CHIP 25.0mm SQ 3.5mm thick HEATSINK LPD60-25B 65.0g CLIP CQZ65-67 (φ2.0) ANCHOR CNCR-12 TIM YG6260 TOTAL FORCE 5.2 kgf (50.8N) 11.8 PSI</p>	<p>[5] PCB 5.0mm thick DUMMY-CHIP 25.0mm SQ 3.5mm thick HEATSINK ULP70-9BM 46.0g CLIP CQZ65-67 (φ2.0) ANCHOR CNCR-16 TIM YG6260 TOTAL FORCE 4.6 kgf (45.2N) 10.5PSI</p>	<p>[6] PCB 5.0mm thick DUMMY-CHIP 25.0mm SQ 3.5mm thick HEATSINK LPD60-25B 65.0g CLIP QSZ64x64 ANCHOR ANCR-20 TIM YG6260 TOTAL FORCE 2.6 kgf (25.4N) 5.9PSI</p>
<p>[7] PCB 5.0mm thick DUMMY-CHIP 25.0mm SQ 5.0mm thick HEATSINK ULP70-13BM 65.0g CLIP QSZ64x64 ANCHOR ANCR-20 TIM YG6260 TOTAL FORCE 2.6 kgf (25.4N) 5.9PSI</p>	<p>[8] PCB 5.0mm thick DUMMY-CHIP 25.0mm SQ 3.5mm thick HEATSINK ULP80-15B 110.0g QSZ CLIP QSZ65x80 (φ2.0) ANCHOR ANCR-16 TIM YG6260 TOTAL FORCE 5.5kgf (53.8N) 12.5PSI</p>	<p>[9] PCB 5.0mm thick DUMMY-CHIP 25mm SQ 3.5mm thick X 2 HEATSINK LPD13070-35BM 210.0g QSZ CLIP QSZ65x80 (φ2.0) ANCHOR ANCR-16 TIM YG6260 TOTAL FORCE 11.0kgf (107.7N) 25.0PSI</p>